

CyberPower®

Model #: OL2000RMXL2U

UPC: 649532832361



Available at
CablesPlus
U ★ S ★ A
<http://www.cablesplususa.com/>
☎ 866-678-5852

The Online Series is designed for those applications requiring maximum power protection. With its double conversion design and Zero transfer time, it provides clean and seamless Pure Sinewave power to the critical loads.

The front LED panel displays all major UPS vitals which significantly increase manageability and ease of control. The Online Series offers three choices for communication including RS232, RS232-USB, or SNMP/AS400 card. Auxiliary battery packs can also be added to these units which boost run-times, in event of a power outage. The input and output EMI filters increase the immunity of the load to disturbances and surges, even in bypass.

The Online Series also incorporates microprocessor-based fully digital control, and include PowerPanel Business Edition™ which gives the user ultimate control and flexibility of power management options. The OL2000RMXL2U comes with 6 (six) 12V/7Ah batteries (72V), and 5 power receptacles (4 x NEMA 5-20R, 1 x NEMA L5-20R).

Through its advanced and smart power management, the Online Series is the ideal power solution for Network, Servers, Telecommunications, Storage, as well as Industrial application protection.

Please note: This unit requires a 20A outlet.

- **Pure Sinewave** – The UPS generates energy that is identical to, or cleaner than the utility company's power grid. Benefits include: low total harmonic distortion, minimal electrical noise, and optimal line clarity.
- **Microprocessor-based Digital Control** – Digital routing is maintained through a network of integrated circuitry and discrete values used for internal system processing, which significantly increase efficiency and responsiveness.
- **RM/T Configuration** – The unit can be mounted either in Tower or Rackmount (2U) form.
- **XL Battery Expansion** - The XL battery expansion port allows for the addition of multiple battery packs to increase back-up time.
- **Dual PC Support** – The unit has 2 (two) communication ports that allow the user full control of dual PCs or servers.
- **LED Front Panel** – Immediate system vital information: load capacity, battery capacity, fault status, and bypass status.
- **PowerPanel Business Edition** – Supporting up to 25 UPS units, the Business Edition also has application/OS shutdown, event logging (power, surge, voltage variations), hibernation mode, internal reports and analysis, and remote management.
- **Metal Housing** – Rigid metal construction allows for placement in areas with a demanding environment.
- **Audible Alarms** - Audible tones identify when the unit is running off battery power, unit overloads and low battery.
- **Resettable Circuit Breaker** - Convenient unit reset switch in case of an overload.
- **3-year Warranty** - CyberPower will replace damaged units if within 3 years of purchase date. We stand behind our products and guarantee quality. CyberPower also offers a #1 rated technical support team that will assist you with product, installation, or warranty concerns --- Free of Charge!
- **ISO & Safety Certifications** - All CyberPower's manufacturing facilities are ISO-9001 Quality Tested. Our products are also certified by the FCC, cUL, and UL.
- **Windows compatibility** - Our power management software has been fully tested and is compatible with Windows 2000, 2003, XP, and Vista x32 & x64.

CablesPlus
U ★ S ★ A

<http://www.cablesplususa.com/>

☎ 866-678-5852

Technical Specifications

General	
Model #	OL2000RML2U
UPS Topology	Online
Input	
Voltage	60 - 142V
Frequency	40 - 70Hz
Plug Type	NEMA 5-20P
Cord Length	6 ft
Output	
VA	2000
Watts	1400
Automatic Voltage Regulation	N/A
On Battery Waveform	Sine Wave
Outlets - Total	5
Outlets - Battery & Surge	4 x NEMA 5-20R, 1 x NEMA L5-20R
Outlets - Surge-Only	None
Transfer Time	0 ms
Battery	
Runtime at Full-Load	7 Minutes
Runtime at Half-Load	18 Minutes
Battery Specification	6 x 12V/7Ah
Surge Protection and Filtering	
Surge Suppression	736 Joules
Phone / Ethernet RJ11 / RJ45	None
Coax Protection RG6	None
Management & Communications	
Indicators	LED Indicators
USB Port	1 x HID Compliant
Serial Port	1 x DB9
Software	PowerPanel Business Edition
SNMP / HTTP Remote Monitoring	Yes [With optional RMCARD301]
Physical	
Dimensions (WxHxD)	17.25" x 3.25" x 26"
Weight	70.1 lbs.
Warranty	
Product Warranty	3-year warranty. Free Tech Support.
Connected Equipment Guarantee	Lifetime
CEG Amount	\$400,000